



CONCRETE:
MIN. C 25

| Product ID | Description | Dimensions [mm] | | | Class BS 5911 | Weight [kg] |
|------------|-------------|-----------------|------|------|---------------|-------------|
| | | Ø A | Ø B | L | | |
| 30010 | CP 300 | 300 | 400 | 2000 | H | 370 |
| 30020 | CP 400 | 400 | 520 | 2000 | H | 495 |
| 30030 | CP 500 | 500 | 600 | 2000 | H | 815 |
| 30040 | CP 600 | 600 | 740 | 2000 | H | 1230 |
| 24010 | CP 800 | 800 | 940 | 2000 | H | 1595 |
| 24080 | CP 800 RF* | 800 | 940 | 2000 | H | 1613 |
| 24020 | CP 900 | 900 | 1060 | 2000 | M / H | 1946 |
| 24090 | CP 900 RF* | 900 | 1060 | 2000 | M / H | 1967 |
| 24030 | CP 1000 | 1000 | 1160 | 2000 | H | 2138 |
| 24060 | CP 1000 RF* | 1000 | 1160 | 2000 | H | 2161 |
| 24040 | CP 1100 | 1100 | 1300 | 2000 | H | 2746 |
| 24070 | CP 1100 RF* | 1100 | 1300 | 2000 | H | 2770 |

* DIFFERENT REINFORCEMENT DESIGNS AVAILABLE.

